



solid solutions to better hardscapes

PO Box 70 • 32020 126th St • Princeton, MN 55371 • Tel 800-752-9326 • Fax 763-389-2725

Ground Cover 100gsm

Product Specification

SRW GC3 Ground Cover is a superior quality, woven geotextile composed of polypropylene materials offering optimum performance when used in stabilization applications. The polypropylene fibers are specially formulated to resist UV light deterioration and are inert to commonly encountered soil chemicals. The fabric will not rot or mildew, is non-biodegradable, and is resistant to damage from insects and rodents. SRW Ground Cover meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Weight (Typical)	ASTM D 5261	Oz yd ²	3.0 oz
Grab Tensile	ASTM D 4632	lbs	150 x 110
Grab Elongation	ASTM D 4533	%	15
Trap Tear	ASTM D 4533	Lbs	60
Puncture	ASTM D 4833	lbs	55
Water Flow Rate	ASTM D 4491	Gpm/sf	9
Permittivity	ASTM D 4491	sec ⁻¹	N/A
UV Resistance	ASTM D 4355	%	70- After 2500 hours

To the best of our knowledge, the information contained herein is accurate. However, SRW Products cannot anticipate all conditions under which SRW product information and our products or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety or suitability of our products either alone or in combination with other products. Final determination of the suitability of any information or material for the use contemplated, or its manner of use, and whether the suggested use infringes any patents is the sole responsibility of the user.