



solid solutions to better hardscapes

PO Box 70 • 32020 126th St • Princeton, MN 55371 • Tel 800-752-9326 • Fax 763-389-2725

SRW Professional (Black, PolySpun)

Product Specification

SRW Professional is a superior quality Polypropylene general purpose fabric used as a weed control, separation, and water flow fabric. Formulated to resist ultraviolet light deterioration, and inert to commonly encountered soil chemicals. The fabric will not rot or mildew, is non-biodegradable, and is resistant to damage from insects and rodents. The design allows for water, air, and nutrients to penetrate to the plants roots in addition to its ability to work behind retaining walls and under patios and walkways.

SRW Professional meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Weight (Typical)	ASTM D 5261	oz/yd ²	3
Grab Tensile	ASTM D 4632	lbs.	58
Mullen Burst Strength	ASTM D 3786	psi	128
Puncture	ASTM D 4833	lbs.	45
Air Permeability	ASTM D 0737	Cu Ft/Min/Ft ²	171
Water Flow	ASTM D 4491	gpm/ft ²	170
UV Resistance	ASTM D 4355	% Strength	71

To the best of our knowledge, the information contained herein is accurate. However, SRW Products cannot anticipate all conditions under which SRW product information and our products or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety or suitability of our products either alone or in combination with other products. Final determination of the suitability of any information or material for the use contemplated, or its manner of use, and whether the suggested use infringes any patents is the sole responsibility of the user.