



solid solutions to better hardscapes

PO Box 70 • 32020 126th St • Princeton, MN 55371 • Tel 800-752-9326 • Fax 763-389-2725

SRW SB3

Product Specification

SRW Products Manufactures/Supplies a 100% Polyester Non-Woven Thermal Bonded Filament Fibers marketed as **SRW SB3**. With excellent dimensional stability and low shrinkage, our Spun Bond products serve as the professional's choice for landscape and geotextile projects. The fabric will not rot or mildew, is non-biodegradable with superior UV resistance, and is resistant to damage from insects and rodents.

SRW SB3 meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Grab Tensile	ASTM D 4632	lbs.	105
Grab Elongation	ASTM D 4632	lbs.	65
Wide Width Tensile	ASTM D 4595	lbs.	260.2
Trap Tear	ASTM D 4533	lbs.	45
Puncture	ASTM D 4833	lbs.	37
Water Flow	ASTM D 4491	gpm/ft ²	114
AOS	ASTM D 4751	US Sieve	45

To the best of our knowledge, the information contained herein is accurate. However, SRW Products cannot anticipate all conditions under which SRW product information and our products or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety or suitability of our products either alone or in combination with other products. Final determination of the suitability of any information or material for the use contemplated, or its manner of use, and whether the suggested use infringes any patents is the sole responsibility of the user.